

DISCOVER THE OLEO-MAC TRACTOR RANGE

OLEO-MAC TRACTOR RANGE

The tractor is the fundamental helper for the care of large gardens, parks and public green areas. In these cases, having an agile and powerful vehicle can make the difference.

Oleo-Mac tractors are **robust and extremely easy to handle**, equipped with **agile steering systems** that allow you to make even very tight turns. The ease of maneuvering near plants and shrubs allows for greater precision and speed in finishing.

They are also able to **adapt their movement based on the type of terrain**. Equipped with **hydrostatic transmission** which allows you to manage the speed by operating a pedal, without the need to stop or with **mechanical lever transmission**.

The different types of engine, **single-cylinder or twin-cylinder**, offer different **powers based on the models**, so as to always make them suitable for the extension and type of surface you intend to cut.



Inquadra il qrcode e scopri di più su www.myoleo-mac.com



Rider

Designed for small and medium surfaces, **up to 4,000 m²**. Compact and easy to handle (they have the engine in the rear position) they allow you to move easily and precisely in gardens with plants or in the presence of obstacles.



Side discharge

Ideal for surfaces of **up to 8,000 m²**, they are characterized by greater construction simplicity as they do not collect grass but simply cut it or chop it using the mulching function.



Rear discharge

They allow you to collect grass using large collection baskets; having cutting widths of up to 125 cm and also being powered by twin-cylinder engines, they can be used on gardens of **up to 9,000 m²**.



Professional all-terrain

Designed for cleaning uncultivated areas with dense vegetation, rough or sloping terrain when grass collection is not necessary. Also available with 4x4 transmission, they can easily cover surfaces of **up to 10,000 m²**.

Rider

Designed for small and medium surfaces, **up to 4,000 m²**. Compact and easy to handle (they have the engine in the rear position) they allow you to move easily and precisely in gardens with plants or in the presence of obstacles.



Plus point



Vertical storage

Save space! You can store the ride-on mower in a vertical position during the storage period.



Electromagnetic clutch

The engagement of the electromagnetic clutch occurs quickly and silently with a simple touch of a convenient button on the control panel.



Telescopic lever for emptying the bag

The telescopic lever is easily reachable from the driver's seat. It allows you to tilt and empty the full bag without any muscular effort and without having to twist your torso.



Lever for cutting height adjustment

The adjustment lever is comfortable and easy to reach, with a graduated scale that lets you see immediately the desired cutting height.

Technical data

| Model |  MISTRAL 72/12,5 K H |  MISTRAL 72/13 H |
|-------------------------|--|--|
| Weight | 192 kg | 192 kg |
| Mulching/Side discharge | optional/optional | standard/standard |
| Plus | < 4000 m ² , 3 cutting device, Deck wash | < 4000 m ² , 4 cutting device, Deck wash |
| Cutting width | 72 cm | 72 cm |
| Speed (km/h) | from 0 to 8.6 km/h in forward drive - from 0 to 3.2 km/h in reverse | from 0 to 8.6 km/h in forward drive - from 0 to 3.2 km/h in reverse |
| Engine make/model | Emak K 1250 AVD | B&S Powerbuilt 3125E AVS series |
| Displacement | 413 cm ³ | 344 cm ³ |
| Turning radius | 45 cm | 45 cm |
| Cutting height | 30-80 mm, 7 positions | 30-80 mm, 7 positions |
| Bag capacity | 180 L | 180 L |
| Number of blades | 1 | 1 |
| Propulsion | hydrostatic | hydrostatic |
| Overall dimensions | 198x73x110 cm | 198x73x110 cm |

Side discharge

Ideal for surfaces of **up to 8,000 m²**, they are characterized by greater construction simplicity as they do not collect grass but simply cut it or chop it using the mulching function.



Plus point



Front bumper

The large steel front bumper provides robustness and solidity, protecting your ride-on mower from accidental impacts.



Quick connector "Deck Wash System"

The quick connector "Deck Wash System", located directly on the mowing deck, allows directing water inside to facilitate cleaning of the mowing apparatus.



Electromagnetic clutch




The electromagnetic clutch engages quickly and quietly, thanks to a convenient button located on the control panel.



Lever for cutting height adjustment

Our handy lever for adjusting the cutting height is within easy reach and equipped with a graduated scale. This feature allows you to immediately see the desired height level, with 7 positions available to achieve the perfect cut.

Technical data

| Model |  OM 99 L/12,5 K M |  OM 99 L/14,5 K |  OM 109 L/16 K |
|-------------------------|---|--|--|
| Number of blades | 2 | 2 | 2 |
| Displacement | 413 cm ³ | 432 cm ³ | 452 cm ³ |
| Cutting height | 30-90 mm, 7 positions | 30-90 mm, 7 positions | 30-90 mm, 7 positions |
| Engine make/model | Emak K 1250 AVD | Emak K 1450 AVD | Emak K 1600 AVD |
| Mulching/Side discharge | standard/standard | standard/standard | standard/standard |
| Turning radius | 45 cm | 45 cm | 45 cm |
| Speed (km/h) | from 1.6 to 8.3 km/h in forward drive - 2.5 km/h in reverse | from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse | from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse |
| Weight | 169 kg | 169 kg | 170 kg |
| Overall dimensions | 172x129x110 cm | 172x129x110 cm | 172x139x110 cm |
| Cutting width | 98 cm | 98 cm | 108 cm |
| Plus | < 6000 m ² , Deck wash | < 6000 m ² , Deck wash | < 8000 m ² , Deck wash |
| Propulsion | hydrostatic | hydrostatic | hydrostatic |

Rear discharge

They allow you to collect grass using large collection baskets; having cutting widths of up to 125 cm and also being powered by twin-cylinder engines, they can be used on gardens of **up to 9,000 m²**.



Plus point



Cruise control

The 125 model comes standard with cruise control, allowing you to set a constant speed, optimizing work time.



Towing hitch included

The standard towing hitch makes your machine even more versatile, allowing you to easily tow a trailer or a lawn roller.



Reduced turning radius

The reduced turning radius allows you to move easily around ornamental plants and shrubs, avoiding unnecessary and difficult reversing or repositioning of the machine.



LED headlights

LED headlights with daytime running light function ensure high visibility even in low light conditions.

Technical data

| Model |  OM 86 R/12,5 K M |  OM 86 R/14,5 K |  OM 92 R/16 K |  OM 95/16 K |  OM 102 R/16 K |  OM 105/16 K |  OM 125/22 V |
|-------------------------|---|---|---|---|---|--|--|
| Number of blades | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Displacement | 413 cm ³ | 432 cm ³ | 452 cm ³ | 452 cm ³ | 452 cm ³ | 452 cm ³ | 656 cm ³ |
| Cutting height | 30-90 mm, 7 positions | 30-90 mm, 7 positions | 30-90 mm, 7 positions | 20-80 mm, 6 positions | 30-90 mm, 7 positions | 30-90 mm, 7 positions | 30-90 mm, 7 positions |
| Engine make/model | Emak K 1250 AVD | Emak K 1450 AVD | Emak K 1600 AVD | Emak K 1600 AVD | Emak K 1600 AVD | Emak K 1600 AVD | B&S V-Twin Intek 7220 OHV series |
| Mulching/Side discharge | standard/not available | standard/not available | standard/not available | standard/not available | standard/not available | standard/not available | standard/not available |
| Turning radius | 45 cm | 45 cm | 45 cm | 75 cm | 45 cm | 75 cm | 70 cm |
| Speed (km/h) | from 1.6 to 7.5 km/h in forward drive - 2.5 km/h in reverse | from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse | from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse | from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse | from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse | from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse | from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse |
| Weight | 190 kg | 190 kg | 192 kg | 230 kg | 194 kg | 240 kg | 275 kg |
| Overall dimensions | 250x96x110 cm | 250x96x110 cm | 250x99x110 cm | 251x117x100 cm | 250x109x110 cm | 251x117x100 cm | 251x119x130 cm |
| Cutting width | 86 cm | 86 cm | 92 cm | 95 cm | 102 cm | 105 cm | 125 cm |
| Bag capacity | 300 L | 300 L | 300 L | 310 L | 300 L | 310 L | 310 L |
| Plus | < 4000 m ² , Deck wash | < 4000 m ² , Deck wash | < 4000 m ² , Deck wash | < 4000 m ² | < 7000 m ² , Deck wash | < 7000 m ² | < 9000 m ² |
| Propulsion | 5 forward speeds + 1 reverse | hydrostatic | hydrostatic | hydrostatic | hydrostatic | hydrostatic | hydrostatic |

Professional all-terrain

Designed for cleaning uncultivated areas with dense vegetation, rough or sloping terrain when grass collection is not necessary. Also available with 4x4 transmission, they can easily cover surfaces of **up to 10,000 m²**.



Plus point



110 cm deck with mulching blades

The CHEYENNE model is equipped with a 110 cm deck featuring 3 rotors and 6 mulching blades. This system finely shreds all types of grass and shrubs, ensuring an effective and clean cut.



Maximum safety guaranteed

The CHEYENNE model comes standard with a rollbar, front and rear bumpers, side protections, and safety belts. These features ensure maximum safety during operations, even in the most complex situations.



Maximum stability on any terrain

The large tread and the low center of gravity of the machine ensure maximum stability, even on steep terrains or near edges and ditches.



Self-locking differential


The self-locking differential ensures maximum traction in any terrain condition and slope.

Technical data

| Model |  APACHE 92 EVO |  APACHE 92 EVO 4x4 |  CHEYENNE 110 4x4 |
|-------------------------|--|---|---|
| Weight | 317 kg | 350 kg | 401 kg |
| Mulching/Side discharge | not available/not available | not available/not available | optional/not available |
| Plus | < 9000 m ² | < 9000 m ² | < 10 000 m ² |
| Cutting width | 92 cm | 92 cm | 110 cm |
| Speed (km/h) | from 0 to 8.5 km/h in forward drive - from 0 to 4.5 km/h in reverse | from 0 to 9.0 km/h in forward drive - from 0 to 5.0 km/h in reverse | from 0 to 9.0 km/h in forward drive - from 0 to 5.0 km/h in reverse |
| Engine make/model | Emak K 2400 AVD V-Twin, B&S Vanguard V-Twin | Emak K 2400 AVD V-Twin, B&S Vanguard V-Twin | B&S Vanguard V-Twin |
| Displacement | 570 cm ³ - 708 cm ³ | 627 cm ³ - 708 cm ³ | 627 cm ³ |
| Turning radius | 65 cm | 65 cm | 73 cm |
| Cutting height | 50-120 mm, 6 positions | 50-120 mm, 6 positions | 40-120 mm, 4 positions |
| Number of blades | 1 | 1 | 3 |
| Propulsion | hydrostatic, self-locking differential | hydrostatic 4x4, self-locking differential | 4x4 hydrostatic - self-locking differential |
| Overall dimensions | 231x101x151 cm | 231x101x151 cm | 235x116x174 cm |


Compatible accessories

Fuel

| | | | | | | | | | | | | | |
|---|-----------------------------|-----------------|---------------------|--|---|--|--|--|--|--|--|--|--|
|  | Petrol jerry can 5 l | 4175169A | Code | | | | | | | | | | |
| | | | MISTRAL 72/12,5 K H | | X | | | | | | | | |
| | | | MISTRAL 72/13 H | | X | | | | | | | | |
| | | | OM 99 L/12,5 K M | | X | | | | | | | | |
| | | | OM 99 L/14,5 K | | X | | | | | | | | |
| | | | OM 109 L/16 K | | X | | | | | | | | |
| | | | OM 86 R/12,5 K M | | X | | | | | | | | |
| | | | OM 86 R/14,5 K | | X | | | | | | | | |
| | | | OM 92 R/16 K | | X | | | | | | | | |
| | | | OM 95/16 K | | X | | | | | | | | |
| | | | OM 102 R/16 K | | X | | | | | | | | |
| | | | OM 105/16 K | | X | | | | | | | | |
| | | | OM 125/22 V | | X | | | | | | | | |
| | | | CHEYENNE 110 4x4 | | X | | | | | | | | |


Battery chargers

For a garden tractor always ready to get started

| | | | | |
|---|-----------------|------|---------------------|--|
|  | Battery charger | Code | MISTRAL 72/12,5 K H | |
| | | | MISTRAL 72/13 H | |
| | | | OM 99 L/12,5 K M | |
| | | | OM 99 L/14,5 K | |
| | | | OM 109 L/16 K | |
| | | | OM 86 R/12,5 K M | |
| | | | OM 86 R/14,5 K | |
| | | | OM 92 R/16 K | |
| | | | OM 95/16 K | |
| | | | OM 102 R/16 K | |
| | | | OM 105/16 K | |
| | | | OM 125/22 V | |
| CHEYENNE 110 4x4 | | | | |


Trailer

A must-have, to exploit the transport capability of garden tractors

| | | | | | | | | | | | | | | | | |
|---|----------------|------------------|------|---------------------|-----------------|------------------|----------------|---------------|------------------|----------------|--------------|------------|---------------|-------------|-------------|------------------|
|  | Trailer | 68130005A | Code | MISTRAL 72/12,5 K H | MISTRAL 72/13 H | OM 99 L/12,5 K M | OM 99 L/14,5 K | OM 109 L/16 K | OM 86 R/12,5 K M | OM 86 R/14,5 K | OM 92 R/16 K | OM 95/16 K | OM 102 R/16 K | OM 105/16 K | OM 125/22 V | CHEYENNE 110 4x4 |
|---|----------------|------------------|------|---------------------|-----------------|------------------|----------------|---------------|------------------|----------------|--------------|------------|---------------|-------------|-------------|------------------|



Snow chains

Work on the snow in complete safety

| | | Code | MISTRAL 72/12,5 K H | MISTRAL 72/13 H | OM 99 L/12,5 K M | OM 99 L/14,5 K | OM 109 L/16 K | OM 86 R/12,5 K M | OM 86 R/14,5 K | OM 92 R/16 K | OM 95/16 K | OM 102 R/16 K | OM 105/16 K | OM 125/22 V | CHEYENNE 110 4x4 |
|---|-------------|----------|---------------------|-----------------|------------------|----------------|---------------|------------------|----------------|--------------|------------|---------------|-------------|-------------|------------------|
|  | Snow chains | 68050026 | - | - | X | X | X | X | X | X | - | X | - | - | - |
| | Snow chains | 68120014 | - | - | - | - | - | - | - | - | X | - | X | X | - |

Discharge deflector

Orderly distribution for better organized work

| | | Code | MISTRAL 72/12,5 K H | MISTRAL 72/13 H | OM 99 L/12,5 K M | OM 99 L/14,5 K | OM 109 L/16 K | OM 86 R/12,5 K M | OM 86 R/14,5 K | OM 92 R/16 K | OM 95/16 K | OM 102 R/16 K | OM 105/16 K | OM 125/22 V | CHEYENNE 110 4x4 |
|---|--------------------|-----------|---------------------|-----------------|------------------|----------------|---------------|------------------|----------------|--------------|------------|---------------|-------------|-------------|------------------|
|  | Side discharge kit | 68132044A | X | - | - | - | - | - | - | - | - | - | - | - | - |
| | Side deflector | 68130591 | - | X | - | - | - | - | - | - | - | - | - | - | - |
|  | Rear deflector | 68130404 | X | X | - | - | - | - | - | - | - | - | - | - | - |
| | Rear deflector | 68050011 | - | - | - | - | - | - | - | - | X | - | X | X | - |

Mulching kit

Order in the garden and food for the lawn

[illegible]



Towing trailer kit

Optimize the power of your garden tractor

[illegible]


Snow blade

Remove snow and ice from footpaths

| | | | | | | | | | | | | | | | |
|---|--------------------------------|----------|---------------------|-----------------|------------------|----------------|---------------|------------------|----------------|--------------|------------|---------------|-------------|-------------|------------------|
| | | Code | MISTRAL 72/12,5 K H | MISTRAL 72/13 H | OM 99 L/12,5 K M | OM 99 L/14,5 K | OM 109 L/16 K | OM 86 R/12,5 K M | OM 86 R/14,5 K | OM 92 R/16 K | OM 95/16 K | OM 102 R/16 K | OM 105/16 K | OM 125/22 V | CHEYENNE 110 4x4 |
|  | Snow blade with rubber scraper | 68050015 | - | - | - | - | - | - | - | - | X | - | X | X | - |
|  | Connection flange snow blade | 68050008 | - | - | - | - | - | - | - | - | X | - | X | X | - |


Steering wheel knob

Convenience and comfort on the move

| | | | |
|---|---------------------|------|---------------------|
|  | Steering wheel knob | Code | MISTRAL 72/12,5 K H |
| | | | MISTRAL 72/13 H |
| | | | OM 99 L/12,5 K M |
| | | | OM 99 L/14,5 K |
| | | | OM 109 L/16 K |
| | | | OM 86 R/12,5 K M |
| | | | OM 86 R/14,5 K |
| | | | OM 92 R/16 K |
| | | | OM 95/16 K |
| | | | OM 102 R/16 K |
| OM 105/16 K | | | |
| OM 125/22 V | | | |
| CHEYENNE 110 4x4 | | | |

Lawn roller

A finishing touch for a uniform and tidy lawn

| | | | | | |
|---|-------------|----------|------|---------------------|--|
|  | Lawn roller | 68050010 | Code | MISTRAL 72/12,5 K H | |
| | | | | MISTRAL 72/13 H | |
| | | | | OM 99 L/12,5 K M | |
| | | | | OM 99 L/14,5 K | |
| | | | | OM 109 L/16 K | |
| | | | | OM 86 R/12,5 K M | |
| | | | | OM 86 R/14,5 K | |
| | | | | OM 92 R/16 K | |
| | | | | OM 95/16 K | |
| | | | | OM 102 R/16 K | |
| | | | | OM 105/16 K | |
| | | | | OM 125/22 V | |
| | | | | CHEYENNE 110 4x4 | |