

ALL-TERRAIN APACHE 85 2WD

Robust and reliable, all-terrain mowing tractors are suitable for large areas of up to 7,000 m². They are designed for clearing overgrown land, rough terrain, and sloping areas where grass collection is not required.

These mowing tractors are equipped with various features that make the operator's work easier, including a hydrostatic transmission operated by a control lever for managing travel direction and speed, an automatic locking differential, and electromagnetic blade engagement. Integrated Cruise Control comes as standard on all models, allowing the tractor to maintain a constant working speed during operation.



All-terrain APACHE 85 flyer

Low centre of gravity engine and seat for enhanced stability and safety
Front-mounted fuel tank for improved weight distribution and reduced heat exposure
Steel footplate with anti-slip embossing for secure footing in all working conditions
Side handles for additional support when operating on slopes
Cup holder and storage compartment

All-terrain APACHE 85 flyer

- Low centre of gravity engine and seat for enhanced stability and safety
- Front-mounted fuel tank for improved weight distribution and reduced heat exposure
- Steel footplate with anti-slip embossing for secure footing in all working conditions
- Side handles for additional support when operating on slopes
- Cup holder and storage compartment



Plus point



Limited-slip differential

Provides improved traction on slopes and challenging terrain, maintaining a stable path even on uneven surfaces. Greater control and safety during operation.



Drive control lever

Drive system with integrated cruise control, ensuring a constant speed while maintaining full machine manoeuvrability. Comfort and precision, even during extended working sessions.



V-twin engine


The high torque of the V-twin engine delivers efficient performance even at high speeds, providing consistent power and excellent working capacity.




Mower deck design

The deck's height and geometry keep the grass circulating for longer, promoting finer and more uniform mulching of the cut material. The result is a cleaner and more effective cut.

Technical data

Model	 APACHE 85 2WD
Displacement	452 cm ³ - 635 cm ³
Cutting width	85 cm
Number of blades	1 (with 2 floating blades)
Engine make/model	Emak K 1600 AVD - Emak K 2000 AVD V-Twin
Cutting height	35-85 mm, 5 positions
Propulsion	hydrostatic, self-locking differential
Speed (km/h)	from 0 to 8.5 km/h in forward drive - from 0 to 4.5 km/h in reverse
Turning radius	78 cm
Overall dimensions	194×93×100 cm
Plus	< 7000 m ²
Mulching/Side discharge	optional/optional
Weight	232 kg

Fuel

		Code	APACHE 85 2WD
	Petrol jerry can 5 l	4175169A	X