

## GSH 370 CHAINSAW

The "H" Series chainsaws represent Oleo-Mac's entry-level range, designed to deliver the perfect balance of performance and value for domestic tasks and light agricultural work.

The range now expands with the all-new **GSH 370**, the most compact and lightweight model in the lineup. Designed for private users, this chainsaw stands out for its innovative design, the high reliability of its components, and class-leading performance.



### GSH 370 petrol chainsaw

The new GSH 370 chainsaws feature a 35.2 cm<sup>3</sup> engine delivering 2.1 HP (1.5 kW) of power. Designed primarily for private users, they are the ideal choice for everyday domestic tasks such as light pruning and cutting firewood for fireplaces and wood-burning stoves. The GSH 370 stands out thanks to a range of technical features that enhance comfort, ease of use, and cutting performance. Its anti-vibration system, consisting of 3 springs and 2 rubber mounts, effectively reduces vibrations transmitted to the operator, while the multifunction control lever, side chain tensioner, and Easy On starting system ensure simple, convenient operation.

# GSH 370 petrol chainsaw

The new GSH 370 chainsaws feature a **35.2 cm<sup>3</sup>** engine delivering **2.1 HP (1.5 kW)** of power. Designed primarily for private users, they are the ideal choice for everyday domestic tasks such as light pruning and cutting firewood for fireplaces and wood-burning stoves.

The GSH 370 stands out thanks to a range of technical features that enhance comfort, ease of use, and cutting performance. Its anti-vibration system, consisting of **3 springs and 2 rubber mounts**, effectively reduces vibrations transmitted to the operator, while the **multifunction control lever**, **side chain tensioner**, and **Easy On starting system** ensure simple, convenient operation.



## Plus point



### Multifunction control lever

The on/off switch, choke and half-throttle control are integrated into a single lever, ensuring maximum convenience and ease of use.



### Primer bulb

By delivering fuel directly to the carburetor, the primer bulb makes cold starts easier after refueling or following extended periods of inactivity.



### High-performance engine

Designed with two piston rings, a forged and machined steel crankshaft and connecting rod, needle bearings, and a chrome-plated cylinder, the engine delivers consistent performance and long-lasting reliability, even under demanding operating conditions.



### Anti-vibration system

Featuring three spring shock absorbers and two rubber bump stops positioned between the control handle and the engine support, the system effectively isolates the operator from vibrations, providing greater comfort during prolonged use.

## Technical data

|                                  |                                                                                                           |
|----------------------------------|-----------------------------------------------------------------------------------------------------------|
| Model                            | <br>GSH 37 / GSH 370 |
| Power/Displacement               | 2.1 HP - 1.5 kW/35.2 cm <sup>3</sup>                                                                      |
| Bar length (nose)                | 14"-16", 35-41 cm                                                                                         |
| Chain (pitch x gauge)            | Oregon 3/8" x .050", Oregon .325" x .050"                                                                 |
| Oil Pump                         | automatic, adjustable, zero flow rate at idle speed                                                       |
| Oil/fuel tank capacity           | 0.22 L/0.32 L                                                                                             |
| Plus                             | EasyOn - User-friendly starting system, Lateral chain tensioner                                           |
| Sound pressure/power level       | 103.2/111.5 dB(A)                                                                                         |
| Lh/rh vibration level            | 5.0/5.7 m/s <sup>2</sup>                                                                                  |
| Dry weight without bar and chain | 4.5 kg                                                                                                    |

Fuel

|                                                                                   |                      | Code     | GSH 37 / GSH 370 |
|-----------------------------------------------------------------------------------|----------------------|----------|------------------|
|  | Petrol jerry can 5 l | 4175169A | X                |

Fuel/Oil

|                                                                                    |              | Code     | GSH 37 / GSH 370 |
|------------------------------------------------------------------------------------|--------------|----------|------------------|
|  | Fuel/oil can | 3355004A | X                |