



It's an Emak S.p.A. trademark  
42011 Bagnolo in Piano (RE) Italy  
Tel. +39 0522 956611 • Fax +39 0522 951555  
[info@myoleomac.com](mailto:info@myoleomac.com) • [www.myoleomac.com](http://www.myoleomac.com)  
YouTube [www.youtube.com/MyOleoMac](http://www.youtube.com/MyOleoMac)

# NEW CHAINSAW GST 360



001102030

PERFORMANCE  
DESIGN  
VERSATILITY





PERFORMANCE



TORQUE AND POWER  
WITH NO LIMIT

DESIGN



NEW DESIGN, ERGONOMICS  
AND BALANCE

VERSATILITY



MULTIPURPOSE,  
NOT JUST PRUNING



**NYLON AIR FILTER**  
Large size filter element for more efficient air intake and reduced maintenance times



**ON-BOARD CLUTCH**  
Quick fitting of bar and chain, cleaner clutch for lasting performance



**ADJUSTABLE ALUMINIUM OIL PUMP**  
Optimal lubrication of bar and chain, even in tough working conditions



**PROFESSIONAL ENGINE**

- Light alloy crankcase
- Nickel plated cylinder
  - Two-ring piston
- Two-part forged crankshaft



**SNAP HOOK**  
Fold away steel snap hook designed for rapid attachment of the tool to the operator's harness



**TRANSLUCENT TANKS**  
Oil and fuel levels can be monitored easily thus reducing unscheduled stops for top-ups



**"EASY ON" FACILITATED STARTING**  
Reduces the compression effect of the professional engine for effortless starts



**ALUMINIUM BAR CASE**  
Greater endurance and performance during the toughest conditions (standard metal spike)



**"ALWAYS-ON" SWITCH**  
Fast stopping and always ready to restart thanks to the spring return function



**AIR PURGE**  
Assists cold starts and starting after refuelling



TECHNICAL SPECIFICATIONS

POWER/DISPLACEMENT	2.0 HP – 1.5 kW/35.1 cm³
BAR LENGTH (nose)	30-35 cm/12"-14" (sprocket)
CHAIN (pitch x gauge)	3/8" x .050" (sprocket)
CHAIN TENSION ADJUSTER	lateral
OILER	adjustable aluminium / zero flow rate at idle speed
OIL RESERVOIR / FUEL TANK CAPACITY	0.23 l/0.28 l
TANK FILLER NECK	Ø 28 (fuel) / Ø 24 (oil)
CLUTCH	On-Board
ON-OFF SYSTEM	Always-On
DRY WEIGHT WITHOUT BAR AND CHAIN	3.8 Kg

PROTECTIVE CLOTHING



Professional protective helmet with integral face shield and noise filtering ear defenders



Jacket with anti-cut protection, resistant to chain speeds of up to 20 m/sec



Tree climbing trousers with anti-cut protection, resistant to chain speeds of up to 20 m/sec



Anti-cut forestry boots with reinforced toecap, resistant to chain speeds of up to 24 m/sec

For sound advice, just ask our authorized dealer.